

LT-ANTD4-300-370-11

4-Element Dipole Array Antenna | 300-370 MHz | 8.15-11.2 dBi


The LT-ANTD4-300-370-11 is a testament to superior engineering and design. Its features, from its optimized frequency range to its impressive power handling capability, make it an outstanding choice for robust two-way radio systems in professional settings.

Features


- Broadband, Low VSWR
- High Gain
- 4-Element Dipole Array Antenna
- 300-Watt High Power
- Pattern Adjustable Offset Circular, Cardioids, or Bidirectional
- PIP: 500W

Applications


- UHF Band TETRA Communications
- Wireless Paging System
- Wireless Data Transmission System
- Wireless Video System



H-plane: Gain 11.2 dBi
1/4 λ spacing from tower



H-plane: Gain 11.2 dBi
1/2 λ spacing from tower



H-plane: Gain 10.6 dBi
3/8 λ spacing from tower

Specifications

LT-ANTD4-300-370-11	
Frequency Range	300-370 MHz
Gain (Dependent on Pattern)	8.5-11.2 dBi
Power Rating	300 W
Impedance	50 Ω
VSWR	≤ 1.5
Vertical Beamwidth	16°

LT-ANTD4-300-370-11	
Polarization	Vertical
Connector	N Female
Dimensions (H x D) mm	3250x600
Weight (Antenna + Clamps)	12.5 Kg
Lightning Protection	DC Grounded
Wind Rating	60 m/s



Support mast is customer-supplied.
Product specifications are subject to change without prior notice.
For more information, visit www.lamatel.ca or send an email to sales@lamatel.com.