

LT-ANTMV-148-168-4.5

VHF Mobile Communication Antenna | 148-168 MHz | 4.5 dBi

LT-ANTMV-148-168-4.5, a premium mobile antenna designed for seamless communication across the 148-168 MHz frequency range. This robust antenna features an NMO mounting system, ensuring easy installation on vehicles or stationary platforms. With gold-plated spring contacts and a solid brass bushing & ferrule in a stylish chrome finish, it is engineered for both aesthetic appeal and lasting durability. The 17-7PH stainless steel whip is built to withstand the rigors of the environment without the need for constant tuning.

Features

- NMO Mounting
- Gold-Plated Spring Contact
- Solid Brass Brushing & Ferrule in Chrome Finish
- Stainless Steel Shock Spring
- 17-7PH Stainless Steel Whip
- No Tuning Needed

Specifications

LT-ANTMV-148-168-4.5	
Frequency Range	148-168 MHz
Antenna Gain	4.5 dBi
Power Rating	160 W
Bandwidth	20 MHz
VSWR	≤ 2.0



LT-ANTMV-148-168-4.5	
Termination	NMO
Length	965 mm
Impedance	50 Ω
Wave	1/2 wave



Product specifications are subject to change without prior notice.
For more information, visit www.lamatel.ca or send an email to sales@lamatel.com.